


## DeckLink 8K Pro Mini



**\$765**

DeckLink 8K Pro Mini is the ultimate 8K digital cinema low profile capture and playback card. Featuring 4 independent 12G-SDI Micro BNC connections, DeckLink 8K Pro Mini can work in all SD, HD, Ultra HD, 4K DCI, 8K and 8K DCI standards. You get support for high frame rate, 12-bit RGB 4:4:4 video and full Rec. 2020 color, making it perfect for next generation high resolution and high dynamic range workflows!

### Connections

#### SDI Video Inputs

4 x bi-directional 12G-SDI Micro BNC connectors.  
Supports SD/HD/2K/4K/8K, single, dual link and quad link 4:2:2/4:4:4. 2D/3D switchable.

#### SDI Video Outputs

4 x bi-directional 12G-SDI Micro BNC connectors.  
Supports SD/HD/2K/4K/8K, single, dual link and quad link 4:2:2/4:4:4. 2D/3D switchable.

#### SDI Audio Outputs

16 Channels embedded in SD/HD/2K.  
64 Channels embedded in 4K/8K.

#### Sync Input


Tri-Sync or Black Burst.

#### SDI Audio Inputs

16 Channels embedded in SD/HD/2K.  
64 Channels embedded in 4K/8K.

#### Computer Interface

PCI Express 8 lane generation 3, compatible with 8 and 16 lane PCI Express slots.



---

## Supported Codecs

AVC-Intra, AVCHD, Canon XF MPEG2,  
Digital SLR, DV-NTSC, DV-PAL,  
DVCPRO50, DVCPROHD, DPX, HDV,  
XDCAM EX, XDCAM HD,  
XDCAM HD422, DNxHR and DNxHD,  
Apple ProRes 4444,  
Apple ProRes 422 HQ,  
Apple ProRes 422, Apple ProRes LT,  
Apple ProRes 422 Proxy,  
Uncompressed 8-bit 4:2:2,  
Uncompressed 10-bit 4:2:2,  
Uncompressed 10-bit 4:4:4.

---

## Software

### Software Included

DaVinci Resolve, Media Express, Disk  
Speed Test, LiveKey, Blackmagic  
Desktop Video Utility and Blackmagic  
driver on Mac OS and Windows.  
Media Express, Blackmagic Desktop  
Video Utility and Blackmagic driver  
on Linux.

### Internal Software Upgrade

Firmware built into software driver.  
Loaded at system start or via  
updater software.

---

## Physical Installation

Low profile PCI Express 8 lane generation 3, compatible with 8, 16 lane PCI Express slots on Mac OS, Windows and Linux.  
Please check the Support pages to see the full system requirements.

---

## Software Applications



DaVinci Resolve



Fusion



Final Cut Pro



Adobe Premiere Pro



Avid Media Composer



Adobe After Effects



Avid Pro Tools



Steinberg Cubase



Autodesk Flame



Adobe Photoshop

**Other supported applications include:** Steinberg Nuendo, Open Broadcaster Software Studio, vMix, The Foundry Nuke, Grass Valley Edius X, Sony Catalyst Production Suite, Tools On Air Just: Play & Live & In, Softron MovieRecorder & MReplay, Adobe Flash Media Live Encoder, Telestream Wirecast, Resolume Arena, Vegas Creative Software Vegas Pro & Vegas Edit, Corel VideoStudio Pro, CyberLink PowerDirector, VidblasterX Studio & Broadcast, CasparCG Server, Magicsoft CG, Xsplit Broadcaster, DevTek Easy Media Suite, Metus Ingest, Boinx Software MimoLive, Cinegy Capture Pro, Renewed Vision ProPresenter, Ventuz Director, Class X Liveboard & Coral CG, Glookast Capturer, Nautilus Studio NEMO3D, Derivative TouchDesigner, Assimilate Scratch & Live Assist, Burst Video WebClip2Go & [REC]Marker, NewBlue Title Live & Titler Pro, SGO Mistika, Zoom.

These are third party applications and support may vary, check with your software vendor.

---

## Video Standards

### SD Video Standards

525i59.94 NTSC, 625i50 PAL

### HD Video Standards

720p50, 720p59.94, 720p60  
1080i50, 1080i59.94, 1080i60  
1080p23.98, 1080p24, 1080p25,  
1080p29.97, 1080p30, 1080p47.95,  
1080p48, 1080p50, 1080p59.94,  
1080p60, 1080p95.90, 1080p96,  
1080p100, 1080p119.88, 1080p120  
1080PsF23.98, 1080PsF24,  
1080PsF25, 1080PsF29.97, 1080PsF30

### 2K Video Standards

2Kp23.98 DCI, 2Kp24 DCI, 2Kp25 DCI,  
2Kp29.97 DCI, 2Kp30 DCI,  
2Kp47.95 DCI, 2Kp48 DCI, 2Kp50 DCI,  
2Kp59.94 DCI, 2Kp60 DCI,  
2Kp95.90 DCI, 2Kp96 DCI,  
2Kp100 DCI, 2Kp119.88 DCI,  
2Kp120 DCI, 2KPsF23.98 DCI,  
2KPsF24 DCI, 2KPsF25 DCI,  
2KPsF29.97 DCI, 2KPsF30 DCI

### Ultra HD Video Standards

2160p23.98, 2160p24, 2160p25,  
2160p29.97, 2160p30, 2160p47.95,  
2160p48, 2160p50, 2160p59.94,  
2160p60, 2160p95.90, 2160p96,  
2160p100, 2160p119.88, 2160p120

### 4K Video Standards

4Kp23.98 DCI, 4Kp24 DCI, 4Kp25 DCI,  
4Kp29.97 DCI, 4Kp30 DCI,  
4Kp47.95 DCI, 4Kp48 DCI, 4Kp50 DCI,  
4Kp59.94 DCI, 4Kp60 DCI,  
4Kp95.90 DCI, 4Kp96 DCI,  
4Kp100 DCI, 4Kp119.88 DCI,  
4Kp120 DCI

### 8K Video Standards

4320p23.98, 4320p24, 4320p25,  
4320p29.97, 4320p30, 4320p47.95,  
4320p48, 4320p50, 4320p59.94,  
4320p60

---

### 8K DCI Video Standards

8Kp23.98 DCI, 8Kp24 DCI, 8Kp25 DCI,  
8Kp29.97 DCI, 8Kp30 DCI,  
8Kp47.95 DCI, 8Kp48 DCI, 8Kp50 DCI,  
8Kp59.94 DCI, 8Kp60 DCI

### 3D SDI Video Standards

720p50, 720p59.94, 720p60  
1080p23.98, 1080p24, 1080p25,  
1080p29.97, 1080p30, 1080p47.95,  
1080p48, 1080p50, 1080p59.94,  
1080p60, 1080p95.90, 1080p96,  
1080p100, 1080p119.88, 1080p120  
1080PsF23.98, 1080PsF24,  
1080PsF25, 1080PsF29.97, 1080PsF30  
1080i50, 1080i59.94, 1080i60  
2Kp23.98 DCI, 2Kp24 DCI, 2Kp25 DCI,  
2Kp29.97 DCI, 2Kp30 DCI,  
2Kp47.95 DCI, 2Kp48 DCI, 2Kp50 DCI ,  
2Kp59.94 DCI, 2Kp60 DCI,  
2Kp95.90 DCI, 2Kp96 DCI,  
2Kp100 DCI, 2Kp119.88 DCI,  
2Kp120 DCI  
2KPsF23.98 DCI, 2KPsF24 DCI,  
2KPsF25 DCI, 2KPsF29.97 DCI,  
2KPsF30 DCI  
4Kp23.98 DCI, 4Kp24 DCI, 4Kp25 DCI,  
4Kp29.97 DCI, 4Kp30 DCI,  
4Kp47.95 DCI, 4Kp48 DCI, 4Kp50 DCI,  
4Kp59.94 DCI, 4Kp60 DCI,  
4Kp95.90 DCI, 4Kp96 DCI,  
4Kp100 DCI, 4Kp119.88 DCI,  
4Kp120 DCI  
2160p23.98, 2160p24, 2160p25,  
2160p29.97, 2160p30, 2160p47.95,  
2160p48, 2160p50, 2160p59.94,  
2160p60, 2160p95.90, 2160p96,  
2160p100, 2160p119.88, 2160p120

### SDI Compliance

SMPTE 259M, SMPTE 274M,  
SMPTE 292M, SMPTE 296M,  
SMPTE 372M, SMPTE 424M,  
SMPTE 425M, SMPTE 2036-1,  
SMPTE 2048-1, SMPTE 2081-10,  
SMPTE 2081-11, SMPTE 2081-12,  
SMPTE 2082-10, SMPTE 2082-11,  
SMPTE 2082-12 and SMPTE ST2108-1

### SDI Metadata Support

RP 188/SMPTE 12M-2 and  
closed captioning.

### Audio Sampling

Television standard sample rate of 48  
kHz at 24-bit.

### SDI Video Sampling

4:2:2, 4:4:4

### SDI Color Precision

8, 10, 12-bit RGB 4:4:4 in all modes up  
to 8Kp30 DCI, and 8, 10-bit YUV 4:2:2  
in all modes.

### Color Space

REC 601, REC 709, REC 2020.

### HDR Support

HDR static metadata packing, HLG  
and PQ transfer characteristics.

### Multiple Rate Support

SDI video connections are switchable  
between SD/HD/2K/4K and 8K.

---

## Processing

### Colorspace Conversion

Hardware based real time on output.

### 3D Processing


Left eye/right eye dual stream  
capture and playback.

### Real Time Effects

DaVinci Resolve, Final Cut Pro internal  
effects. Adobe Premiere Pro CC  
Mercury Playback Engine effects. Avid  
Media Composer internal effects.

---

## Physical Specifications



---

## Operating Systems



Mac 14.0 Sonoma,  
Mac 15.0 Sequoia or later.



Windows 10, 64-bit.  
Windows 11.



Linux

---

## Power Requirements

### Power Consumption

18 W

---

## Environmental Specifications

### Operating Temperature

5° to 50° C (41° to 122° F)

### Storage Temperature

-20° to 60° C (-4° to 140° F)

### Relative Humidity

0% to 90% non-condensing

---

## What's Included

DeckLink 8K Pro Mini

---

## Warranty

3 Year Limited Manufacturer's Warranty.

All items on this website are copyright Blackmagic Design Pty. Ltd. 2025, all rights reserved. All trademarks are property of their respective owners. MSRP includes duties, but excludes sales tax and shipping costs. This website uses remarketing services to advertise on third party websites to previous visitors to our site. You can opt out at any time by changing cookie settings. [Privacy Policy](#)

Blackmagic Design Authorized Reseller