

# Mini Converter SDI to Audio 4K



Mini Converter SDI to Audio 4K includes everything you need to de-embed 4 channels of analog audio or 8 channels of AES/EBU digital audio from any SDI video connection. Now you can access the audio in any SDI video connection for output to a massive range of audio equipment such as audio mixers, analog broadcast decks, audio monitors and more!

**\$359**

## Connections

### SDI Video Inputs

1 x SD, HD or 6G-SDI. 1 x ALT SDI Input for automatic switch over if main input fails.

### SDI Video Outputs

1 x SDI Video Loop Output.

### SDI Redundant Inputs

Automatically switches over if main SDI input is lost.

### Analog Audio Outputs

4 channels of professional balanced analog audio with standard 1/4 inch jack connections.

### Digital Audio Outputs

8 channels of professional balanced digital with standard 1/4 inch jack connections.

### Multi Rate Support

Auto detection SD, HD or 6G-SDI.

### Updates and Configuration

USB

### Reclocking

Yes



## Standards

### SD Video Standards

525i59.94 NTSC, 625i50 PAL

---

**HD Video Standards**

720p50, 720p59.94, 720p60,  
1080p23.98, 1080p24, 1080p25,  
1080p29.97, 1080p30, 1080p50,  
1080p59.94, 1080p60, 1080PsF23.98,  
1080PsF24, 1080PsF25,  
1080PsF29.97, 1080PsF30, 1080i50,  
1080i59.94, 1080i60

**2K Video Standards**

2K DCI 23.98p, 2K DCI 24p,  
2K DCI 25p, 2K DCI 23.98PsF,  
2K DCI 24PsF, 2K DCI 25PsF

**Ultra HD Video Standards**

2160p23.98, 2160p24, 2160p25,  
2160p29.97, 2160p30

**4K Video Standards**

4K DCI 23.98p, 4K DCI 24p,  
4K DCI 25p

**SDI Compliance**

SMPTE 259M, SMPTE 292M,  
SMPTE 296M, SMPTE 372M,  
SMPTE ST-2081, ITU-R BT.656  
and ITU-R BT.601

**SDI Video Rates**

SDI video inputs are automatically  
detected between standard definition  
and high definition.

**SDI Video Sampling**

4:2:2, 4:4:4

**SDI Audio Sampling**

Television standard sample rate of  
48 kHz and 24 bit.

**SDI Color Precision**

4:2:2, 4:4:4

**SDI Color Space**

YUV, RGB

**SDI Auto Switching**

Automatically selects between SD,  
HD, 3G and 6G-SDI.

---

## Software

**Software Control**

Mac™ and Windows™ software  
upgrade via USB.

**Internal Software Upgrade**

Via included updater application.

---

## Operating Systems



Mac 10.15 Catalina,  
Mac 11.1 Big Sur or later.



Windows 10, 64-bit.

---

## Settings Control

Mini Switches or USB software.

---

## Power Requirements

**Power Supply**

+12V universal power supply included  
with international socket adapters for  
most countries. Cable tie point.

**Power Consumption**

5.52 Watts

**Operational Voltage Range**

12V - 31V DC

---

---

## Physical Specifications



---

## Environmental Specifications

### Operating temperature

0° to 40° C (32° to 104° F)

### Storage temperature

-20° to 45° C (-4° to 113° F)

### Relative Humidity

0% to 90% non-condensing

---

## What's Included

Mini Converter SDI to Audio 4K

12V universal power supply with international socket adapters

---

## Warranty

3 Year Limited Manufacturer's Warranty.

All items on this website are copyright Blackmagic Design Pty. Ltd. 2025, all rights reserved. All trademarks are property of their respective owners. MSRP includes duties, but excludes sales tax and shipping costs. This website uses remarketing services to advertise on third party websites to previous visitors to our site. You can opt out at any time by changing cookie settings. [Privacy Policy](#)

Blackmagic Design Authorized Reseller